

Comtech Backup Rod

APPLICATIONS:

- Used as an expansion joint and filler for precast, steel, Aluminum and concrete projects.
- Used as a filter for decoration purpose.

Technical Properties:

PROPERTIES	UNIT	VALUE	TEST METHOD
Density	g/cm ³	0.04	ASTM D-792
Cell Size	mm	0.82	ASTM D-3576
Water Absorption	mg/cm ²	0.08	ASTM D-570
Moisture Permeability	g/cm ² .24hr	0.5	ASTM D-570
Elongation At Break	%	60	ASTM D-638
Thermal Conductivity	W/m ² .°C	0.0406	ASTM D-5930
Permanent Compression Set (100 KGf/CM ²)	%	1-2	Special Method

Packaging:

DIMENSION	STANDARD PACKAGING/BAG
10	800 m/Bag (8 PCs 100 m)
15	360 m/Bag (6 PCs 60 m)
20	200 m/Bag (4 PCs 50 m)
25	100 m/Bag (4 PCs 25 m)
30	100 m/Bag (4 PCs 25 m)

Middle East Bldg. Chemical Ind. LLC

P.O.Box47611, Sharjah, UAE.

E-mail: comtech2@eim.ae

Tel. (9716) 544 18 73 Fax (9716) 544 18 79